CP-DW10N

HITACHI
Inspire the Next

Closed Captioning | AMX Device Discovery | Crestron Integrated Partner | Campus Notification System™

Key Features

- Short throw 60" for 100" screen
- Networking, control/ maintenance and security
- 2,000 ANSI lumens
- 4,000 hour hybrid filter
- Template function
- 10 watt speaker
- Input source naming
- Transition detector
- Audio pass through
- Power saving mode
- Blackboard whiteboard mode
- PJ Messenger

Specifications

Model Name		CP-DW10N Series
Liquid Crystal Panel Structure		0.59" P-Si TFT x 3
Number of Pixels		1,024,000 pixels
Resolution	Video	540 TV lines
	RGB	1280 dots X 800 lines
Colors		16.7 million colors
Aspect Ratio		Native 16:10/4:3 compatible
Lens		Digital Zoom x 1.3
Throw Ratio (distance : width)		0.5 (Fixed)
Lamp		180W UHB
Brightness		2,000 ANSI Lumens
Expected lamp Life		Approx. 3,000 hours(normal), 4,000 hours(Eco Mode)
Contrast Ratio		400 : 1
Speaker Output		10W
Power Supply		AC100 - 120V / AC220 - 240V 50/60 Hz
Power Consumption		270W
Operating Temperature		5℃ - 35℃ (41℉ - 95℉)
Input Signals	RGB	VGA, SVGA, XGA, WXGA, SXGA, SXGA+, UXGA, MAC 16"
	Composite Video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60
	Component Video	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Acoustic Noise Level		36 dB (28 dB in Eco Mode)
H-Sync		15 KHz - 106 KHz
V-Sync		50 Hz - 120 Hz
Vertical Keystone		+ / - 6°
Approvals		UL, C-UL, FCC, CE, RoHS
RGB Input	Analog RGB	15pin Mini-Dsub x 2
RGB Output	RGB	15pin Mini-Dsub x 1
Digital Input	RGB	HDMI x 1
Video Input	S-Video	Mini DIN 4-pin connector x 1
	Composite Video	RCA jack x 1
	Component Video	Shared with VGA 15pin D-Sub
Audio	Input	Stereo Mini jack x 2, RCA(L/R) x 1 pair
	Output	RCA(L/R) x 1 pair
Ethernet		RJ-45
Control Terminals		9-pin D-sub connector x 1 (RS-232 control)
Dimensions (W x D x H)		13.1" x 11.9" x 4.1"
Weight		8.2 lbs.
Additional Features		MyScreen, My Memory, My Button, My Text, My Source, Blackboard/ Whiteboard Mode, Day Time Mode, Input Source Naming(English), Resolution Setting, Template, Closed Caption, Audio Pass Through, Network Bridge,
Supplied Accessories		Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual, Security Label
Lamp		CPD10LAMP (DT01091)
Remote Control		HL02483 (Optional RC-R008 with laser pointer)
Filter		UX35971

Screen Size 16:10 Throw Distance

Diagonal*	Width*	Distance*
60	51	25
63	53	26
70	59	29
77	65	33
80	68	34
90	76	38
100	85	43

Throw Ratio: 0.5:1 (distance : width)
*Measured in inches